



PRODUCT DATA

Acoustics & Vibration Instruments

Sound Level Calibrator

Model AWA6022A

FEATURES

- ☼ Comply with IEC 60942 class 2
- ☼ Pocket size, portable unit
- ☼ Frequency 1000Hz, give independence of weighting

USES

- ☼ Calibration of sound level meters
- ☼ Calibration of other sound measurement equipments.



Specifications

PERFORMANCE SPECIFICATIONS

Normal sound pressure level: 94 & 114dB

Normal frequency: 1000Hz

Sound level accuracy: ± 0.5 dB

Frequency accuracy: ± 1 Hz

Distortion(THD): ≤ 1 %

POWER SUPPLY

Power : 2 \times 1.5V alkaline battery LR6 (AA)

BATTERY CHECK

As long as the signal continue for one minute after the contact is release, otherwise battery low

ENVIRONMENT

Operating Temperature: -10°C ~ +50°C

Humidity: 25% ~ 90%(RH)

Atmospheric Pressure: 65 kPa ~ 108 kPa

PHYSICAL

Dimensions: 70mm \times 70mm \times 35.2 mm

Weight: 120 g (include battery)

Microphone Type: 1/2" and 1/4" (with supplied adaptor)

ACCESSORIES:

Included: 2 \times 1.5V alkaline battery LR6 (AA)

Instruction Manual x 1

Adaptor for 1/4" microphone \times 1

case \times 1

We keep the right to change all specifications and included accessories without notice

Hangzhou Aihua Instruments Co., Ltd.

Headquarters

No.37 Xianxing Rd, Yuhang District, Hangzhou, Zhejiang, China 311122

Tel.: +86 (571) 85021931 Fax: +86 (571) 85022955

Email: yqf@hzaihua.com

<http://www.hzaihua.com>